# PACCAR PX-9





# PROVEN PERFORMANCE. SUPERIOR RESULTS. PERFECT FIT.



The 8.9-liter PACCAR PX-9 engine has one of the highest power-to-weight ratios in its class, with heavy-duty features like replaceable wet liners, roller cam followers, bypass oil filtration and targeted piston-cooling.

Available in both medium and heavy-duty configurations this engine delivers the durability and efficiency needed to lower operating expenses, reduce maintenance and increase productivity.

160

# **RATINGS**

Engine Horsepower	Peak Torque lb-ft @ RPM	GOVERNED RPM
260	720 @ 1,300	2,200
270	800 @ 1,300	2,200
300°	860 @ 1,300	2,200 —
330°	1,000 @ 1,400	2,200
345*	1,150 @ 1,400	2,100
350	1,000 @ 1,400	2,200
370°	1,250 @ 1,400	2,100
380°	1,250 @ 1,400	2,100
400 <sup>‡</sup>	1,250 @ 1,400	2,200
450 <sup>‡</sup>	1,250 @ 1,400	2,200

<sup>\*</sup> Also Fire Service Rating ‡ Fire Service Rating Only


## **SPECIFICATIONS**

Configuration	INLINE 6-CYLINDER
BORE X STROKE (MM)	114 x 145
DISPLACEMENT	8.9 liters
DRY WEIGHT	1,695 lbs.
OIL SYSTEM CAPACITY	24 U.S. quarts
Horsepower	260-450 нр
Peak Torque	720-1,250 lbft.
GOVERNED SPEED	2,100-2,200 RPM
CLUTCH ENGAGEMENT TORQUE <sup>†</sup>	500 lbft. @ 700 rpm
Base Warranty <sup>§</sup>	2 Years/250,000 miles/400,000 km

 $<sup>^{\</sup>scriptscriptstyle \dagger}$ Determined By Engine Horsepower And Idle Setting

## MAINTENANCE INTERVALS

Maintenance Item	MILES	Kilometers
FUEL FILTER	15,000	24,000
OIL AND FILTER	15,000	24,000
COOLANT FILTER (IF EQUIPPED)	15,000	24,000
DEF FILTER	200,000	320,000





ENGINE SPEED (RPM)





PACCAR Inc P.O. Box 1518 Bellevue, WA 98009 2013PACCARPX9SPEC/12



160

2.200

<sup>§</sup>Extended Protection Plans Available